



Dongguan Xintai Instrument Co., Ltd.
Professional Instrument Manufacturer

CFM/CMM Thermo-Anemometer **HT-9819**

Anemometer is mainly used in electric power, iron and steel, petrochemicals, energy and other industries.

Specification

Air Velocity	range	resolution	Accuracy
m/s	0.40~30.00m/s	0.01m/s	±(3%+0.20m/s)
km/h	1.4~108.0km/h	0.1km/h	±(3%+0.8km/hr)
ft/min	80~5900ft/min	1ft/min	±(3%+40ft/m)
mph	0.9~67.0mph	0.1mph	±(3%+0.4MPH)
knots	0.8to58.0knots	0.1knots	±(3%+0.4knots)
Air flow	range	resolution	Area
CMM	0~9999m ³ /min	1	0~9.999m ²
CFM	0~ft ³ /min	1	0~9.999ft ²
Air temperature	range	resolution	Accuracy
	14~140°F, (-10~60°C)	0.1°F/°C	4.0°F(2.0°C)
Operating Voltage	9V		
Weight	240g		
Size	202×85×48mm		
Accessories	BATTERY, manual black box and gift box.		



HT-9819



ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@neonics.co.th หรือ sale@tools.in.th