

Significance of Use

Corrosion can occur in many key areas of a boiler. It can shorten the life of a boiler, or at the very least, increase the costs associated with maintaining a boiler. Corrosion can form in water heaters, deaerators, superheater tubes, and economizers, among other places. Monitoring the alkalinity, chloride, hardness, dissolved oxygen, phosphate, and sulfite concentrations in cooling and boiler systems is essential in preventing hazardous or costly situations.

HI3821

Cooling and Boiler Test Kit

The HI3821 is a chemical test kit that determines that uses titration and colorimetry to measure six parameters common to cooling and boiler systems: alkalinity, chloride, hardness, dissolved oxygen, phosphate, and sulfite. The HI3821 is supplied with all of the necessary reagents and equipment to perform each analysis, and all reagents are individually available as they run out.

Complete setup

 All required materials are included with the test kit, such as the dissolved oxygen glass bottle, sample beaker, indicator and reagent bottles and packets, and color comparison cube.

High resolution

 All tests provide a high resolution based on the expected range of measurement.

Replacement reagents available

 There is no need to buy a new kit when reagents are exhausted.
 The reagents for each parameter can be ordered individually.

Specifications	HI3821 Cooling	and Boiler	Combination	lest Kit
----------------	----------------	------------	-------------	----------

Specifications	This delication is a second first that the second first t						
Test	Туре	Range	Smallest Increment	Method	Number of Tests		
Alkalinity (as CaCO₃)	titration	0-100 mg/L (ppm) 0-300 mg/L (ppm)	1 mg/L (ppm) 3 mg/L (ppm)	phenolphthalein/ bromphenol blue	110 avg.		
Chloride (as Cl ⁻)	titration	0-100 mg/L (ppm) 0-1000 mg/L (ppm)	1 mg/L (ppm) 10 mg/L (ppm)	mercuric nitrate	110 avg.		
Hardness (as CaCO₃)	titration	0.0-30.0 mg/L (ppm) 0-300 mg/L (ppm)	0.3 mg/L (ppm) 3 mg/L (ppm)	EDTA	100 avg.		
Phosphate (as PO¾-)	colorimetric	0-5 mg/L (pp <mark>m)</mark>	1 mg/L (ppm)	ascorbic acid	50 avg		
Oxygen, Dissolved	titration	0.0-10.0 mg/L (ppm)	0.1 mg/L (ppm)	modified Winkler	110 avg.		
Sulfite (as Na₂SO₃)	titration	0.0-20.0 mg/L (ppm) 0-200 mg/L (ppm)	0.2 mg/L (ppm) 2 mg/L (ppm)	iodometric	110 avg.		
Dimensions	440 x 330 x 100 mm (17.3 x 13.0 x 3.9")						
Ordering Information	HI3821 test kit includes all of the necessary reagents and accessories to perform over 100 tests for every parameter, with the exception of phosphate, which includes reagents for 50 tests, hard carrying case and instructions.						
Reagents	HI3811-100 Alkalinity (as CaCO ₃), 110 tests avg. HI3815-100 Chloride, 110 tests avg.		HI3833-050 Phosphate, 50 tests avg. HI3810-100 Dissolved Oxygen, 110 tests avg.				
3	HI3812-100 Hardne	ss, total (as CaCO ₃), 100 tests avg.	HI3822-100 Sulfite (as Na ₂ SO ₃), 110 tests avg.				

ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@neonics.co.th หรือ sale@tools.in.th

