

## Formaldehyde Meter **HT-502**



Formaldehyde Meter is widely used in factory, workshop, green house, clean room, industry and agriculture, wine bar, hotel, hospital, shop market, airport, railway station, entertainment hall and movie theater etc.

### Specification

Large LCD Display	Color display with backlight
Logger mode	key start/stop, Immediately, Schedule, Real-time&Roll-over
Carbon Dioxide(CO2)	
Range	0~5.000mg/m <sup>3</sup>
Accuracy	±5% or ±0.02mg/m <sup>3</sup> , ±10% ±0.02mg/m <sup>3</sup>
Response time	10s
Temperature Range	-10~70°C(14~158°F)
Resolution	0.1°C/°F
Accuracy	±0.6°C/±0.9°F(0~50°C/32~122°F), others ±1.2°C
Humidity Range	0.1~99.9%RH
Resolution	0.1%
Accuracy	±0.3°C(10~50°C) others are ±1.2°C
Logging Memory	27000
Operating Condition	0~85%RH
Storage Condition	-20~60°C, 0~90%RH
Sensor life	3years
Storage temp	40~70°C(40~ 158°F)
Battery	3.7V rechargeable Li-ion polymer battery
Size	107×107×59mm



**HT-502**



Formaldehyde Structure – CH<sub>2</sub>O

