

Digital Anemometer



GM8908



GM816



GM816A

- 【1】 Measurement of wind velocity, temperature and flow
- 【2】 Selection among max wind speed/min wind speed/average wind speed/current wind speed.
- 【3】 Temperature unit selection between °C/°F
- 【4】 Inlet area set
- 【5】 Selection speed unit among M/S, KM/H, FT/MIN, KNOTS and MPH
- 【6】 Reading hold
- 【7】 LCD backlight
- 【8】 Manual/automatic turning off
- 【9】 Beaufort scale
- 【10】 Wind chill alert
- 【11】 Retractable drag rod
- 【12】 Low battery indication

Technical indicators	GM8908	GM816	GM816A
Wind speed measurement range	0~30m/s; Precision: ±1.5%		
wind temperature measurement range	-10~40°C, (14~113°F); Precision: ±2°C		
Resolution	0.2°C, 0.1m/s		
Peculiarity			
Frozen tip	√		
Max/Avg/current value	√		
Beaufort scale	√		
°C/°F Selection	√		
Backlight	√		
Auto power-off	14 minutes without any operating automatic shutdown		
Conventional			
Power supply	CR2032 3.0V	CR2032 3.0V	6F22 9v
Product size	104.3*57.8*19.9mm	105*18*40mm	160*35.5*52.5mm
Product weight	58.9g(+batteries)	67.8(+batteries)	136g(+batteries)

This unit is an ideal tool for windsurfing, sailing, fishing, kite flying and mountaineering. You can also use it for industrial and home purposes such as measuring wind speed and temperature of CPU computer fans, air-conditioners, air blower etc..

LINE ID:@neonics



ติดต่อบริษัท เนโอเนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@neonics.co.th หรือ sale@tools.in.th