



HI98318

GroLine EC/TDS Tester

- Waterproof
- Automatic temperature compensation (ATC)
- Automatic one-point EC calibration
- Measurement stability indicator

The GroLine waterproof EC/TDS tester is ideal for hydroponics, greenhouses, or anywhere you need quick and accurate conductivity measurements.



Exposed temperature sensor

HI98318 features an exposed temperature sensor for faster response times.



Watertight seal

An easily removable cover provides access to the battery compartment.



Supplied in a carrying case with calibration solutions.

Specifications

	HI98318
EC/TDS	Range 0.0 to 6.00 mS/cm; 0 to 3000 ppm (0.5); 0 to 4000 ppm (0.7)
	Resolution 0.01 mS/cm; 10 ppm (0.5); 10 ppm (0.7)
	Accuracy (@25°C/77°F) ±2% F.S.
	Calibration automatic, one-point (1.41 mS)
	Quick Calibration one-point calibration using HI5036 or HI50036P Quick Cal calibration solution
	TDS Conversion Factor (CF)* 0.5 (500 ppm) or 0.7 (700 ppm)
Temperature	Range 0.0 to 50.0°C/32.0 to 122.0°F
	Resolution 0.1°C/0.1°F
	Accuracy (@25°C/77°F) ±0.5°C/±1°F
Additional Specifications	Temperature Compensation automatic, 0.0 to 50.0°C (32 to 122°F)
	Battery Type / Life CR2032 Li-ion (Included) / approx. 250 hours of continuous use
	Auto-off 8 minutes, 60 minutes, or can be disabled
	Environment 0 to 50°C (32 to 122°F); RH 100% max
	Dimensions 160 x 40 x 17 mm (6.3 x 1.6 x 0.7")
	Weight 75 g (2.6 oz.)
Ordering Information	HI98318 GroLine EC/TDS tester is supplied with Quick Cal calibration sachets (4), battery, storage cap, instruction manual and quality certificate.

EC/TDS solutions begin on page 5.34; Quick Cal solutions begin on page 5.38

ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@neonics.co.th หรือ sale@tools.in.th

HANNA
Instruments