

## Humidity & Temperature Meter



**GM1361**



**GM1361+ (藍牙)**

This unit features stable performance, reliable safety, low power consumption and high precision, be widely applied in the fields of manufacturing, laboratory, logistics, food and hygiene, air-conditioning engineering and environment protection.

Technical indicators	GM1361	GM1361+
Temperature Range	-50 ~ 1200°C(-30~1000°C K-type)	
Temp Accuracy	±1°C or ±1.8°F	
Humidity measurement range	10 ~ 98%RH	
Value accuracy	±3%(30~95%);±5%(10~30%)	
Temperature resolution	0.1°C	
Humidity resolution	0.1%RH	
Sampling frequency	2.0 times/SEC	
Operating environment	-10~50°C ( 14 ~122°F ) ≤80%RH No condensation	
Storage environment	-20~60°C ( - 4 ~104°F ) 0%RH~90%RH	
<b>Peculiarity</b>		
Bluetooth communication(App)	×	√
Record 999 groups of data	√	√
°C/°F Selection	√	√
Keeping data	√	√
MAX/MIN/AVG	√	√
K type thermocouple test	√	√
Large screen display	√	√
Automatic/manual to turn it off	√	√
<b>Conventional</b>		
Power supply	4*1.5V AAA batteries	
Product size	106*236.7*37.99mm	
Product weight	287.4g (+batteries)	
Standard Quantity Per Carton	20PCS	
Standard Carton Size	67.5*45.8*30.2cm	
Standard Carton Gross Weight	20.5kg	

NEW