

NON-CONTACT INFRARED THERMOMETERS

MS6530/MS6530A/MS6530B

MS6530

TEMPERATURE
-20°C~537°C
-4°F~999°F



MS6530A

TEMPERATURE
-20°C~850°C
-4°F~1562°F



MS6530B

TEMPERATURE
-20°C~320°C
-4°F~608°F



Features:

- ▶ Distance to Spot 12:1
- ▶ Built-In Laser Pointer to Target Spot
- ▶ Large Temperature Range
- ▶ 0.1°F/°C max resolution
- ▶ Display Back Light



Specifications	MS6530	MS6530A	MS6530B
Specifications			
Temperature Range	-20°C~537°C -4°F~999°F	-20°C~850°C -4°F~1562°F	-20°C~320°C -4°F~608°F
Temperature Resolution	±0.1°C / ±0.1°F	±0.1°C / ±0.1°F	±0.1°C / ±0.1°F
Repeatability	±0.5°C or ±0.5%	±0.5°C or ±0.5%	±0.5°C or ±0.5%
Distance to Spot (D : S)	12 : 1	12 : 1	12 : 1
°C / °F Selection	●	●	●
Emissivity	0.95	0.95	0.95
Laser Target Pointer	●	●	●
Reading Hold	●	●	●
MAX, MIN, AVG, DIF	●	●	●
Display Backlight	●	●	●
Low Battery Display	●	●	●
General			
Power Supply	1×9V 6F22 Battery		
Product Size	190mm×125mm×55mm/7.48"×4.9"×2.16"		
Product Weight	262g/0.57lb		
Certificate	CE RoHS		

ติดต่อบริษัท เนอนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@neonics.co.th หรือ sale@tools.in.th