

Ultrasonic Thickness Gauge



ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th หรือ sale@tools.in.th

SPECIFICATIONS	AS840	AS850	AS860
Transducer	Φ10mm 5MHz	Φ10mm 5MHz / 2.5MHz	Φ6mm 5MHz / Φ10mm 5MHz
Measuring Range	1.2~225mm(Steel)	1.2~225mm(Steel)	1.2~225mm(Steel)
Accuracy	±(1%H±0.1mm)	±(1%H±0.1mm)	±(1%H±0.1mm)
Resolution	0.1mm	0.1mm	0.1mm
Sound Velocity	1000~9999m/s	1000~9999m/s	1000~9999m/s
Operating Frequency	5MHz	5MHz	5MHz
Operation Condition	0°C~40°C	0°C~40°C	0°C~40°C
Minimum Limit For Tube Measuring		Φ20*3mm(Steel)	
Thickness Data Storage	10 groups	10 groups	12 groups
Sound Velocity Measuring & Storage	12 groups	12 groups	12 groups
Backlight Display	√	√	√
Auto Zero Calibration	√	√	√
Auto linear compensation	√	√	---
Coupling Indicator	√	√	√
Battery Indication	√	√	√
Auto/Manual Power Off	√	√	√
Max / Min Thickness Alarm Setup	---	---	√
12 Sound Velocities For Different Material	---	---	√
Metric / Imperial Switchable	---	---	√

GENERAL CHARACTERISTICS & PACKING INFORMATION			
Power	9V battery	9V battery	9V battery
Product Net Weight	200g	210g	240g
Product Size	150 x 80.5 x 34mm	150 x 80.5 x 34mm	150 x 80.5 x 34mm
Packing	Gift box	Gift box	Gift box
Standard Quantity / Carton	24	10	10
Standard Carton Size	47 x 38 x 55cm	39x 32 x 44cm	39x 32 x 44cm
Standard Carton Gross Weight	19.5kg	11.0kg	11.0kg

Differential Pressure Meter Film / Coating Thickness Gauge

SPECIFICATIONS	AS510	SPECIFICATIONS	AS930	AS931
Measuring Range	0~100hPa 0~45.15 inH ₂ O	Measuring Range	0~1800µm	
		Measuring Principle	Magnetic Induction	
Accuracy	±0.03 hPa(0~0.30hPa) ±0.05 hPa(0.31~1.0hPa) ±(1.5%+0.1hPa) remaining ±0.01 inH ₂ O(0.00~0.12inH ₂ O) ±0.02 inH ₂ O(0.13~0.40inH ₂ O) ±(1.5%+0.4inH ₂ O) remaining	Accuracy	±(3%H±1µm)	
		Resolution	0.1µm / 1µm	
Resolution	0.01hPa / 0.01inH ₂ O	Minimum Curvature Radius	Convex=1.5mm Concave=9mm	
Measuring speed	0.5 sec	Base Sample Diameter	Φ7mm	
Units	hPa, mbar, mmH ₂ O, mmHg, inH ₂ O, inHG, m/s, fpm	Base Substrate Thickness	0.5mm	
Operation Condition	0~50°C / 32~122°F	Backlight Display	√	√
		Alarm Buzzer	√	√
		Zero / Two Point / Basic Calibration	√	√
		Single / Continuous / Standard Deviation Measurement	√	√
		Data Storage & Recall	√	√
		Data Analysis	√	√
		Max & Min Measuring	√	√
		AVG & DFR Measuring	√	√
		Data Storage	15 groups	15 groups
		Metric / Imperial Switchable	√	√
		Battery Indication	√	√
		Auto Power Off	√	√
		Operation Condition	0°C~40°C (without strong magnetic)	

GENERAL CHARACTERISTICS & PACKING INFORMATION			
Power	3*1.5V AAA batteries	Power	9V battery
Product Net Weight	71.5g	Product Net Weight	147g
Product Size	124.8 x 49.8 x 25.6mm	Product Size	183x67x30mm
Packing	Gift box	Packing	Gift box
Standard Quantity / Carton	40	Standard Quantity / Carton	10
Standard Carton Size	52.5 x 40 x 49cm	Standard Carton Size	39x32x44cm
Standard Carton Gross Weight	19.01kg	Standard Carton Gross Weight	9.35kg



Ultrasonic Thickness Gauge
AS850
1.2~225mm



Ultrasonic Thickness Gauge
AS860
1.2~225mm



Ultrasonic Thickness Gauge
AS840
1.2~225mm



Differential Pressure Meter
AS510
0~100hPa
0~40.15inH₂O



Film / Coating Thickness Gauge
AS930
0~1800µm



Film / Coating Thickness Gauge
AS931
0~1800µm

*The parameters and specifications are based on products sold.

Ultrasonic Thickness Gauge

SPECIFICATIONS	AR850	AR860
Transducer	Φ10mm 5MHz Φ10mm 2.5MHz	Φ6mm 5MHz Φ10mm 5MHz
Measuring Range	1.2~225mm(Steel)	1.00~300mm(Steel)
Accuracy	±(1%H±0.1mm)	±(1%H±0.1mm)
Resolution	0.1mm	0.1mm
Sound Velocity	1000~9999m/s	1000~9999m/s
Operating Frequency	5MHz / 2.5MHz	5MHz
Operation Condition	0°C~40°C	0°C~40°C
Minimum Limit For Tube Measuring	Φ20 x 3mm(Steel)	Φ15 x 2mm(Steel) (Φ6) Φ20 x 3mm(Steel) (Φ10)
Data Storage	10 groups	12 groups
Sound Velocity Measuring & Storage	12 groups	12 groups
Backlight Display	√	√
Auto Zero Calibration	√	√
Auto linear compensation	√	√
Coupling Indicator	√	√
Battery Indication	√	√
Auto/Manual Power Off	√	√
Max / Min Thickness Alarm Setup	---	√
12 Sound Velocities For Diff. Material	---	√

GENERAL CHARACTERISTICS & PACKING INFORMATION		
Power	3*1.5V AAA batteries	3*1.5V AAA batteries
Product Net Weight	275g	275g
Product Size	153 x 75 x 35mm	153 x 75 x 35mm
Packing	Gift box	Gift box
Sld Quantity / Carton	12	12
Sld Carton Size	52 x 43 x 32.5cm	52 x 43 x 32.5cm
Sld Carton Gross Weight	16.3kg	16.3kg

Film / Coating Thickness Gauge

SPECIFICATIONS	AR930	AR931	AR932
Measuring Range	0~1800μm		0~1500μm
Measuring Principle	Magnetic Induction		Magnetic Induction & Eddy current
Accuracy	±(3%H±1μm)		±(1.8%μm±2μm)(0-500μm) ; ±(2.2%μm±2μm) (500-1500μm)
Resolution	0.1μm / 1μm		0.1μm / 1μm
Minimum Curvature Radius	Convex=1.5mm Concave=9mm		Convex=5mm Concave=30mm
Base Sample Diameter	Φ7mm		25x25mm
Base Substrate Thickness	0.5mm		Magnetic : 0.2mm ; Non-magnetic : 0.05mm
Auto-identify Substrate Material	---	---	√
Backlight Display	√	√	√
Alarm Buzzer	√	√	√
Zero / Two Point / Basic Calibration	√	√	√
Single / Continuous / Standard Deviation Measurement	√	√	√
Data Storage & Recall	√	√	√
Data Analysis	√	√	√
Max & Min Measuring	√	√	√
AVG & DFR Measuring	√	√	√
Data Storage	15 groups	15 groups	20 groups
Metric / Imperial Switchable	√	√	√
Battery Indication	√	√	√
Auto Power Off	√	√	√
Operation Condition	0°C~40°C (without strong magnetic)		0°C~50°C (without strong magnetic)

GENERAL CHARACTERISTICS & PACKING INFORMATION			
Power	9V battery	9V battery	2*1.5V AAA batteries
Product Net Weight	147g	245g	75g
Product Size	183 x 67 x 30mm	153 x 75 x 35mm	119 x 50 x 30mm
Packing	Aluminum Box	Aluminum Box	Gift box
Sld Quantity / Carton	12	12	40
Sld Carton Size	52 x 43 x 32.5cm	52 x 43 x 32.5cm	52.5 x 40 x 49cm
Standard Carton Gross Weight	13.5kg	13.5kg	20kg



Ultrasonic Thickness Gauge
AR850
1.2~225mm



Ultrasonic Thickness Gauge
AR860
1.0~300mm



Film / Coating Thickness Gauge
AR930
0~1800μm



Film / Coating Thickness Gauge
AR931
0~1800μm



Film / Coating Thickness Gauge
AR932
0~1500μm

