

GAS CONTROL PANEL

DR-ZJ200



Shandong Dory Electronic Technology Co.,LTD

26F, Building 3, Longao Jinzuo, Lixia District, Jinan City 250014, Shandong Province, P.R.China


ติดต่อบริษัท เนโอนิกส์ จำกัด

Tel: 098-479-5684 หรือ 061-826-8939 E-mail: sale@neonics.co.th เว็บไซต์: www.neonics.co.th

INSTALLATION INSTRUCTIONS

RS485		Channel 4		Channel 3		Channel 2		Channel 1		Output 1		Output 2	
B	A	24	S	24	S	24	S	24	S	NC	COM	NC	COM
⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕

Control panel



Detector

Gas Controller



Gas Detector

PRODUCT FEATURES



LED display



Fault self-test



Extended output



Intelligent setting



Rich interfaces



Wall mounting

TECHNICAL PARAMETERS

PARAMETER TYPE	PARAMETER
Support channel	1-4 unit
Display type	LED
Input signal	4-20mA
Output signal:	RS485
Connection mode	3-wire
Alarm volume	≥90db
Using environment	-20°C ~ 50°C (0-95)%RH
Power supply	220V(195-235VAC/50-60HZ)
Product weight	3.0Kg
Way to install	Wall mounting(non-explosion-proof place)
Alarm type	Sound and light+Indicator light alarm
Product size	310*200*80mm
Cable specification	RVV/P 3x1.0mm ²
Relay output	2 sets passive NO/COM/NC
Data storage	x
Spare battery	x

